

# SAFETY DATA SHEET

Butyl Gum

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : Butyl Gum  
**Product code** : BTLG-125/10#  
**Product description** : Not available.  
**Product type** : Solid.  
**Other means of identification** : Not available.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

### 1.3 Details of the supplier of the safety data sheet

**Distributor** : Tech Europe 15 Ballinderry Road, Lisburn, BT28 2SA, UK, info@techeurope.co.uk, Chemtrec UK - +(44)-870-8200418  
**Manufacturer** : Tech International, 200 East Coshocton Street, Johnstown, Ohio 43031, 740-967-9015 CHEMTREC: 1-800-424-9300  
**e-mail address of person responsible for this SDS** : jsellers@techtirerepairs.com

### 1.4 Emergency telephone number

#### National advisory body/Poison Center

**Telephone number** : CHEMTREC Italy: 800-789-767  
 CHEMTREC Italy (Milan): +(39)-0245557031

#### Supplier

**Telephone number** : +44 2892 665721  
**Hours of operation** : 0900 - 1700 GMT  
**Information limitations** : Safety Data Sheet

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification** : Carc. Cat. 2; R45  
 R43  
 N; R50/53

**Human health hazards** : May cause cancer. May cause sensitization by skin contact.

**Environmental hazards** : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Date of issue/Date of revision** : 4/14/2014.

1/14

## SECTION 2: Hazards identification

### 2.2.1 Label elements

Hazard pictograms :



Signal word :

Danger

Hazard statements :

May cause an allergic skin reaction.  
May cause cancer.  
Very toxic to aquatic life.  
Toxic to aquatic life with long lasting effects.

### Precautionary statements

General :

Not applicable.

Prevention :

Obtain special instructions before use. Wear protective gloves. Avoid release to the environment.

Response :

IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water.

Storage :

Store locked up.

Disposal :

Dispose of contents and container in accordance with all local, regional, national and international regulations.

### 2.2.2 Label elements

Hazard symbol or symbols :



Indication of danger :

Toxic, Dangerous for the environment

Risk phrases :

R45- May cause cancer.  
R43- May cause sensitization by skin contact.  
R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases :

S53- Avoid exposure - obtain special instructions before use.  
S24- Avoid contact with skin.  
S37- Wear suitable gloves.  
S61- Avoid release to the environment. Refer to special instructions/safety data sheet.

Hazardous ingredients :

Distillates (petroleum), hydrotreated heavy paraffinic di(benzothiazol-2-yl) disulphide

Supplemental label elements :

Not applicable.

### Special packaging requirements

Containers to be fitted with child-resistant fastenings :

Not applicable.

Tactile warning of danger :

Not applicable.

### 2.3 Other hazards

Other hazards which do not result in classification :

None known.

Butyl Gum

### SECTION 3: Composition/information on ingredients

Substance/mixture : Mixture

| Product/ingredient name                                | Identifiers   | %               | Classification   |  | Type |
|--|---|-----------------|--|--|------|
|  |   |                 | 67/548/EEC   | Regulation (EC) No. 1272/2008 [CLP]  |      |
| Distillates (petroleum), hydrotreated heavy paraffinic | EC: 265-157-1<br>CAS: 64742-54-7<br>Index: 649-467-00-8 | >=5,<br><10     | Carc. Cat. 2; R45  | Carc. 1B, H350   | [1]  |
| di(benzothiazol-2-yl) disulphide                       | EC: 204-424-9<br>CAS: 120-78-5<br>Index: 613-135-00-0   | >=1,<br><2.5    | R43, R31<br>N; R50/53  | Skin Sens. 1, H317<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410   | [1]  |
| zinc oxide   | EC: 215-222-5<br>CAS: 1314-13-2<br>Index: 030-013-00-7  | >=0.25,<br><2.5 | N; R50/53  | Eye Irrit. 2, H319<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410   | [1]  |
| thiram (ISO)   | EC: 205-286-2<br>CAS: 137-26-8<br>Index: 006-005-00-4   | >=0.25,<br><1   | Xn; R20/22, R48/22<br>Xi; R36/38<br>R43<br>N; R50/53                     | Acute Tox. 4, H302<br>Acute Tox. 2, H330<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Skin Sens. 1, H317<br>STOT RE 2, H373<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 | [1]  |
|  |   |                 | <b>See Section 16 for the full text of the R-phrases declared above.</b> | <b>See Section 16 for the full text of the H statements declared above.</b>  |      |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

Note L: This component has been tested by Supplier. According to Supplier, the component complies with the criteria of Note L in Annex I of 67/548/EEC, and is exempt from a classification of T; R45. (Contains less than 3% DMSO) See "Section 11: Toxicological Information" for information regarding the classification of substances. The classification for aspiration hazards (R65), does not apply for products placed on the market in aerosol containers. (EU-Directive 67/548 Annex VI 9.4)

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Date of issue/Date of revision : 4/14/2014.

3/14

## SECTION 4: First aid measures

- Inhalation** : Get medical attention immediately. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : May cause sensitization by skin contact.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

Butyl Gum

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : No specific fire or explosion hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
 carbon dioxide  
 carbon monoxide  
 nitrogen oxides  
 sulfur oxides  
 metal oxide/oxides

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. This material is very toxic to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also Section 8 for additional information on hygiene measures.

### 6.2 Environmental precautions

- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and materials for containment and cleaning up

- Small spill** : Move containers from spill area. Avoid dust generation. Place spilled material in a designated, labeled waste container. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision : 4/14/2014.

5/14

Butyl Gum

## SECTION 6: Accidental release measures

- Large spill** : Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. Refer to special instructions/safety data sheet. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

- : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### 7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

No exposure limit value known.

## SECTION 8: Exposure controls/personal protection

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### Derived effect levels

No DELs available.

### Predicted effect concentrations

No PECs available.

## 8.2 Exposure controls

**Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.



Butyl Gum

## SECTION 8: Exposure controls/personal protection

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Solid.  
**Color** : Black.  
**Odor** : Not available.  
**Odor threshold** : Not available.  
**pH** : Not available.  
**Melting point/freezing point** : Not available.  
**Initial boiling point and boiling range** : Not available.  
**Flash point** : Closed cup: Not applicable.  
**Evaporation rate** : Not applicable.  
**Flammability (solid, gas)** : Not available.  
**Burning time** : Not available.  
**Burning rate** : Not available.  
**Upper/lower flammability or explosive limits** : Not available.  
**Vapor pressure** : Not available.  
**Vapor density** : Not available.  
**Relative density** : Not available.  
**Solubility(ies)** : Not available.  
**Partition coefficient: n-octanol/ water** : Not available.  
**Auto-ignition temperature** : Not applicable.  
**Decomposition temperature** : Not available.  
**Viscosity** : Dynamic (room temperature): Not applicable.  
**VOC content** : 0.409 lbs/gal (49 g/l)  
**Explosive properties** : Not available.  
**Oxidizing properties** : Not available.

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**Date of issue/Date of revision** : 4/14/2014.

8/14



Butyl Gum

## SECTION 10: Stability and reactivity

**10.4 Conditions to avoid** : No specific data.

**10.5 Incompatible materials** : No specific data.

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

| Product/ingredient name          | Result                          | Species | Dose                  | Exposure |
|----------------------------------|---------------------------------|---------|-----------------------|----------|
| di(benzothiazol-2-yl) disulphide | LD50 Dermal                     | Rabbit  | >7940 mg/kg           | -        |
| thiram (ISO)                     | LD50 Oral                       | Rat     | >12 g/kg              | -        |
|                                  | LC50 Inhalation Dusts and mists | Rat     | 500 mg/m <sup>3</sup> | 4 hours  |
|                                  | LD50 Dermal                     | Rat     | >5000 mg/kg           | -        |
|                                  | LD50 Oral                       | Rat     | 560 mg/kg             | -        |

**Conclusion/Summary** : Not available.

| Route | ATE value |
|-------|-----------|
|       |           |

#### Irritation/Corrosion

| Product/ingredient name | Result                   | Species | Score | Exposure                | Observation |
|-------------------------|--------------------------|---------|-------|-------------------------|-------------|
| zinc oxide              | Eyes - Mild irritant     | Rabbit  | -     | 24 hours 500 milligrams | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 24 hours 500 milligrams | -           |
| thiram (ISO)            | Eyes - Mild irritant     | Rabbit  | -     | 100 milligrams          | -           |
|                         | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 100 milligrams | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 100 Percent             | -           |

**Conclusion/Summary** : Not available.

#### Sensitization

**Conclusion/Summary** : Not available.

#### Mutagenicity

**Conclusion/Summary** : Not available.

#### Carcinogenicity

**Conclusion/Summary** : Not available.

#### Reproductive toxicity

**Conclusion/Summary** : Not available.

#### Teratogenicity

**Conclusion/Summary** : Not available.

**Information on the likely routes of exposure** : Not available.

#### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.

**Date of issue/Date of revision** : 4/14/2014.

9/14

Butyl Gum

## SECTION 11: Toxicological information

- Inhalation** : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : May cause sensitization by skin contact.
- Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

- Conclusion/Summary** : Not available.
- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

**Other information** : Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

| Product/ingredient name | Result                              | Species  | Exposure |
|-------------------------|-------------------------------------|--|----------|
| zinc oxide              | Acute EC50 0.042 mg/l Fresh water   | Algae - Pseudokirchneriella subcapitata - Exponential growth phase | 72 hours |
|                         | Acute LC50 98 µg/l Fresh water      | Daphnia - Daphnia magna - Neonate                                  | 48 hours |
|                         | Acute LC50 1.1 ppm Fresh water      | Fish - Oncorhynchus mykiss   | 96 hours |
|                         | Chronic NOEC 0.017 mg/l Fresh water | Algae - Pseudokirchneriella subcapitata - Exponential growth phase | 72 hours |
| thiram (ISO)            | Acute EC50 1000 µg/l Fresh water    | Algae - Chlorella pyrenoidosa                                      | 96 hours |
|                         | Acute EC50 0.04 mg/l Marine water   | Algae - Nannochloropsis oculata                                    | 72 hours |

**Date of issue/Date of revision** : 4/14/2014.

10/14

Butyl Gum

## SECTION 12: Ecological information

|  |                                   |   |          |
|--|-----------------------------------|---|----------|
|  | Acute LC50 0.02 mg/l Marine water | Crustaceans - Artemia franciscana - Nauplii | 48 hours |
|  | Acute LC50 0.01 mg/l Fresh water  | Daphnia - Daphnia magna - Neonate           | 48 hours |
|  | Acute LC50 0.3 µg/l Fresh water   | Fish - Cyprinus carpio - Larvae             | 96 hours |

**Conclusion/Summary** : Not available.

### 12.2 Persistence and degradability

**Conclusion/Summary** : Not available.

### 12.3 Bioaccumulative potential

| Product/ingredient name          | LogP <sub>ow</sub> | BCF  | Potential |
|----------------------------------|--------------------|------|-----------|
| di(benzothiazol-2-yl) disulphide | 4.5                | 26.3 | low       |
| thiram (ISO)                     | 1.73               | 3.39 | low       |

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

**PBT** : Not applicable.

**vPvB** : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**Date of issue/Date of revision** : 4/14/2014.

11/14

Butyl Gum

## SECTION 14: Transport information

|                                 | ADR/RID   | ADN   | IMDG  | IATA  |
|---------------------------------|---|---|---|---|
| 14.1 UN number                  | UN3077  | UN3077  | UN3077  | UN3077  |
| 14.2 UN proper shipping name    | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (zinc oxide) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (zinc oxide) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (zinc oxide) | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (zinc oxide) |
| 14.3 Transport hazard class(es) | 9<br>   | 9<br>   | 9<br>   | 9<br>   |
| 14.4 Packing group              | III   | III   | III   | III   |
| 14.5 Environmental hazards      | Yes.  | Yes.  | Yes.  | Yes.  |
| Additional information          | <b>Tunnel code</b><br>(E)                                       | -   | -   | -   |

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorization

##### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Restricted to professional users.

##### Other EU regulations

**Europe inventory** : Not determined.

**Black List Chemicals** : Not listed

**Priority List Chemicals** : Listed

**Integrated pollution prevention and control list (IPPC) - Air** : Not listed

**Integrated pollution prevention and control list (IPPC) - Water** : Not listed

**Date of issue/Date of revision** : 4/14/2014.

12/14

Butyl Gum

## SECTION 15: Regulatory information

| Product/ingredient name                                | Carcinogenic effects | Mutagenic effects | Developmental effects | Fertility effects |
|--|----------------------|-------------------|-----------------------|-------------------|
| Distillates (petroleum), hydrotreated heavy paraffinic | Carc. Cat. 2; R45    | -                 | -                     | -                 |

### National regulations

**D.Lgs. 152/06** : Not classified.

**Chemical Weapons Convention List Schedule I Chemicals** : Not listed

**Chemical Weapons Convention List Schedule II Chemicals** : Not listed

**Chemical Weapons Convention List Schedule III Chemicals** : Not listed

**15.2 Chemical Safety Assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number

### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317  
 Carc. 1B, H350  
 Aquatic Acute 1, H400  
 Aquatic Chronic 2, H411

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification          | Justification      |
|-------------------------|--------------------|
| Skin Sens. 1, H317      | Calculation method |
| Carc. 1B, H350          | Calculation method |
| Aquatic Acute 1, H400   | Calculation method |
| Aquatic Chronic 2, H411 | Calculation method |

**Full text of abbreviated H statements** : H302 Harmful if swallowed.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H330 Fatal if inhaled.  
 H350 May cause cancer.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.  
 H411 Toxic to aquatic life with long lasting effects.

**Date of issue/Date of revision** : 4/14/2014.

13/14

Butyl Gum

## SECTION 16: Other information

**Full text of classifications [CLP/GHS]** : Acute Tox. 2, H330 ACUTE TOXICITY: INHALATION - Category 2  
 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
 Aquatic Acute 1, H400 AQUATIC HAZARD (ACUTE) - Category 1  
 Aquatic Chronic 1, H410 AQUATIC HAZARD (LONG-TERM) - Category 1  
 Aquatic Chronic 2, H411 AQUATIC HAZARD (LONG-TERM) - Category 2  
 Carc. 1B, H350 CARCINOGENICITY - Category 1B  
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
 STOT RE 2, H373 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

**Full text of abbreviated R phrases** : R45- May cause cancer.  
 R20/22- Also harmful by inhalation and if swallowed.  
 R48/22- Also harmful: danger of serious damage to health by prolonged exposure if swallowed.  
 R36/38- Irritating to eyes and skin.  
 R43- May cause sensitization by skin contact.  
 R31- Contact with acids liberates toxic gas.  
 R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Full text of classifications [DSD/DPD]** : Carc. Cat. 2 - Carcinogen category 2  
 Xn - Harmful  
 Xi - Irritant  
 N - Dangerous for the environment

**Date of printing** : 4/14/2014.

**Date of issue/ Date of revision** : 4/14/2014.

**Date of previous issue** : No previous validation.

**Version** : 0.01

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

**Date of issue/Date of revision** : 4/14/2014.

14/14