

APPLICATION CHART FOR MONAFLEX COMPACT OTR VULCANISING SYSTEM (RADIAL/BIAS PLY)
TYRE RANGE: OTR 13.00 TO 55.5/85-63 TRACTOR / OTR & WIDE BASE

Tractor/Wide Base	Tyre Section	Cylinder Bag	Inside Flat Bag	Inside Heat Pad		Outside Heat Pad	External Pack With Flat Bag & Straps
				Bias	Radial		
14.4-24 to 16.9-38	13.00 to 17.5	TR1315/20W		M2519H	M3015H	TR2621H	TR2621E with TROC5XL Straps
18.4-34 to 20.8-42	18.00 to 21.00	M1721/24W		M2519H M2626H	M3015H	TR2621H	TR2621E with TROC5XL Straps
23.1-26 to 30.5-32	23.5 to 26.5	M1721/24W	M4824W	M2519H M2626H	M3015H	TR2621H	TR2621E with TROC5XL Straps
25/65-25	27.00 to 29.5-25/29	M1721/24W	M4824W M5432W	M2519H M2626H	M3015H M4220H	TR2621H	TR2621E with TROC5XL Straps
	29.5-35	M2732/32W		M2519H M2626H	M3015H M4220H	M2626H	M4832E with M45/6/7 (1HG) 6 Straps
65/40-39 to 64/45-45	33.00 to 37.5	M2732/32W	M5432W	M2626H M3132H	M4220H M4224H	M2626H	M4832E with M45/6/7 (1HG) 6 Straps
49.5/85-57 to 50/65-51	40.00	M3842/32W		M3132H	M4220H M4224H	M2626H	M4832E with M45/6/7 (1HG) 6 Straps
46/90-57		M3842/32W	*M5432W		M4824H M5224H		
50/80-57 to 55/80-57		M4447/32W		M3132H	M4220H M4224H M4824H M5224H	M2626H	M4832E with M45/6/7 (1HG) 6 Straps
53.5/85-57 53.5/85-63 55.5/80-57 55.5/85-57 55.5/85-63		M4447/32W	M7532W	M3132H	M4220H M4224H M4824H M5224H	M2626H	M4832E with M45/6/7 (1HG) 6 Straps

RECOMMENDED CONTROL PANEL(S) MC COMPACT or M100

SELECT INSIDE HEAT PAD FROM THOSE LISTED ACCORDING TO PATCH SIZE

BIAS	MAXIMUM PATCH SIZE		RADIAL	MAXIMUM PATCH SIZE	
M2519	23" x 17"	584 x 432mm	M3015	28" x 13"	711 x 330mm
M2626	24" x 24"	610 x 610mm	M4220	40" x 18"	1016 x 457mm
M3132	29" x 30"	737 x 762mm	M4224	40" x 22"	1016 x 559mm
			M4824	46" x 22"	1168 x 559mm
			M5224	50" x 22"	1270 x 559mm

46/90R-57 * It may be necessary to use the M5432W flat bag to fill out the tyre.

14-Mar-05